

Canfield Select Collection

52 In Canfield Select LED Ceiling Fan BSS

300026BSS (Brushed Stainless Steel)

Project Name: _____
 Location: _____
 Type: _____
 Qty: _____
 Comments: _____

Product Information

Product ID	300026BSS
Finish	Brushed Stainless Steel
Blade Finish	Medium Oak/Dark Oak
Collection	Canfield Select Collection

Specifications

Number of Blades	5
Blades Included	Yes
Blade Pitch	14 Degrees
Blade Sweep	52"
Blades Reversible	No
Blade Material	WOOD
Optional Blades Available	No
Downrod 1	1.00 OD X 4.50
Primary Control System	Pull Chain
Remote Included	No
Wall Control Included	Yes
Low Ceiling Adaptable	No
Lead Wire Length	78.00"
Motor Size	172MM X 20MM
Motor Type	AC



Dimensions



Downrod	A	B	C	D
1.00 OD X 4.50	17.50	11.00	11.00	6.25

Downlight

Downlight Included	Yes
Light Source	LED
Downlight Bulb Included	Integrated
Downlight Bulb Type	LED
# of Bulbs/LED Modules	1
Watts	58/12
Initial Lumens	1600
Glass Description	White Cased Opal W/ Clear Outside
Optional Light Kit Available	No
Kelvin Temperature	3000K
Color Rendering Index	80

Safety Listings & Certifications

Safety Rated	Dry
Warranty	www.kichler.com/warranty

Available Finishes

Finish	Fixture	Glass	Blade 1	Blade 2

Installation

The electrical junction box

Canfield Select Collection

52 In Canfield Select LED Ceiling Fan BSS

300026BSS (Brushed Stainless Steel)

Project Name: _____

Location: _____

Type: _____

Qty: _____

Comments: _____

Finish	Fixture	Glass	Blade 1	Blade 2
Brushed Stainless Steel	300026BSS	WHITE CASED OPAL W/ CLEAR OUTSIDE	MEDIUM OAK	DARK OAK
Oil Brushed Bronze	300026OBB	WHITE CASED OPAL W/ CLEAR OUTSIDE	CHERRY	WALNUT

Installation requirements and support structure must be securely mounted and capable of reliably supporting a minimum of 50 pounds. Use only ETL/UL listed electrical junction boxes marked ""For Fan Support""

Electrical Requirements 120v 60Hz ac

Hanging Weight 28.60 LBS

Minimum Distance Between Bottom Of Fan Blade To Floor 7 feet

Notes:

1) Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.

2) Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.